




- PX-4 is designed and manufactured in USA with **2100** effective lumen of the latest in high-brightness LED technology.
- PX-4 with its all-machined/cast chassis, polycarbonate/glass lens cover, and stainless steel mounting bracket, is designed for use in harsh environments where an extreme high-brightness output and reliability is required.
- Built-in thermal management with a state of the art current driver provides optimum light output and a life span that exceeds 50K hours.



Light Source

4 CREE XM-L2 Diodes

LED Options:

Cool White	5000K CCT	CRI >70
Warm White	2700K CCT	CRI >80

50,000 hours average life time

Construction

Machined 6063-T5 aluminum/ Die cast aluminum alloy A360

Mounting Bracket

Stainless steel mounting bracket
• 4mm thickness

LED Driver

12/24V state of the art driver

Parameter	Min	Typical	Max	Unit
Voltage	10	24	28	V
Power		20		W
Mean Lumens		2,100		lm

Protection

- Built-in active thermal management
- Reverse voltage protection
- Under-voltage shutdown
- Transient voltage suppression
- IP 67/68
- EMI filtration

Optics

Flood 30°

Power Connector

Deutsch power connector

Ambient Operating Temperature

-40°C to +70°C

IES File

Call PTLX Global at 1-800-397-7859

Weight

Weight 1.3 lb (0.59 kg)

Ordering Information

Please see ordering chart or contact us for details.



8750, 1598, CSA 22.2 No.250.0-08